



NO.	PART NAME	MATERIAL
1	BODY	CSTL ASTM A216 GR.WCB
2	SCREEN	
	PERF. DIA. MESH	
3	COVER	CSTL ASTM A216 GR.WCB
4	YOKE	DUCTILE IRON
5	YOKE SCREW	STEEL
6	O-RING	BUNA-N
7	STUD	STEEL
8	DRAIN PLUG	CARBON STEEL
9	BODY PLUG	CARBON STEEL

**NOTES:**

1. INLET/OUTLET 150 LB. RAISED FACED FLANGED CONNECTIONS PER ANSI B16.5.
2. 5/8" DIAMETER SLOTTED FOOT PADS FOR 8" SIZE.
3. DIMENSION "G" (NPT) IS FOR DRAIN PLUG, ITEM 8.
4. ITEM 9, BODY PLUG IS NOT TO BE USED AS DRAIN.
5. MAX. WORKING PRESSURE: 200 PSI @ 100° F (13.8 BAR @ 37.8° C)

CUSTOMER:  
P. O. NO.:  
REG. NO.:  
QUOTE NO.:  
TAG NO.:

PIPE SIZE (NOMINAL)	DIMENSIONS									WEIGHT (DRY) LBS. KGS.	PART NO.						
	A		B		C		D		F			G (NOM.)	H	J			
	IN.	MM.	IN.	MM.	IN.	MM.	IN.	MM.	IN.	MM.	IN.	MM.					
8" (200mm)	27.00	686	40.00	1016	16	406	27.00	686	60	1524	1/2 (15)	15.75	400	8.50	216	550/ 249	ST0720800R3C

**Monarch Asia Pacific - Brisbane, Australia**  
web: [www.monarchasiapacific.com.au](http://www.monarchasiapacific.com.au)

**PSF Equipment - Bangkok, Thailand**  
web: [www.psfthailand.com](http://www.psfthailand.com)

<b>FATON</b>	NAME						
	MODEL 72 SIMPLEX STRAINER 150# RAISED FACE FLANGE SIZE 8" CARBON STEEL						
DRAWN	FM	DATE	1/25/95	CERT.	LF	DATE	1/25/95
SIZE	DWG	SD072029			REV	D	
A	NO						

UNAUTHORIZED USE, MANUFACTURE OR REPRODUCTION IN WHOLE OR IN PART IS PROHIBITED.

ELECTRONIC FILE NAME: SD072029.DWG  
REF. ECR 0048143 DATE 09/20/10