



NO.	PART NAME	MATERIAL
1	BODY	SSTL ASTM A351 GR. CF8M
2	SCREEN	
	PERF. DIA. MESH	
3	COVER	SSTL ASTM A351 GR. CF8M
4	YOKE	DUCTILE IRON
5	YOKE SCREW	STEEL
6	O-RING	VITON
7	STUD	STEEL
8	DRAIN PLUG	STAINLESS STEEL
9	BODY PLUG	STAINLESS STEEL

NOTES:

1. INLET/OUTLET 150 LB. RAISED FACED FLANGED CONNECTIONS PER ANSI B16.5.
2. 5/8" DIAMETER SLOTTED FOOT PADS FOR 8" SIZE.
3. DIMENSION "G" (NPT) IS FOR DRAIN PLUG, ITEM 8.
4. ITEM 9, BODY PLUG IS NOT TO BE USED AS DRAIN.
5. MAX. WORKING PRESSURE: 200 PSI @ 100° F
(13.8 B 37.8° C)

CUSTOMER:
P. O. NO.:
REG. NO.:
QUOTE NO.:
TAG NO.:

PIPE SIZE (NOMINAL)	DIMENSIONS									WEIGHT (DRY) LBS. KGS.	PART NO.
	A IN. MM.	B IN. MM.	C IN. MM.	D IN. MM.	F IN. MM.	G (NOM.) IN. MM.	H IN. MM.	J IN. MM.			
8" (200mm)	27.00 / 686	40.00 / 1016	16 / 406	27.00 / 686	60 / 1524	1/2 (15)	15.75 / 400	8.50 / 216	550 / 249	ST0720800R2C	

Monarch Asia Pacific - Brisbane, Australia
web: www.monarchasiapacific.com.au

PSF Equipment - Bangkok, Thailand
web: www.psfthailand.com

FATON	NAME		
	MODEL 72 SIMPLEX STRAINER 150# RAISED FACE FLANGE SIZE 8" STAINLESS STEEL		
DRAWN	FM	DATE	1/25/95
CERT.	LF	DATE	1/25/95
SIZE	DWG NO	SD072030	
A			REV D

UNAUTHORIZED USE, MANUFACTURE OR REPRODUCTION IN WHOLE OR IN PART IS PROHIBITED.

ELECTRONIC FILE NAME: SD072030.DWG
REF. ECR 0048143 DATE 09/20/10