

NEW PRODUCT PREVIEW

HPD Series Pulsation Dampener


1/2" TO 1" PVC, CPVC OR PVDF

KEY FEATURES & BENEFITS

- Corrosion Resistant Construction
- Available in PVC, CPVC, and PVDF Materials
- 316 SS Charging Tee and Gauge
- Multiple Bladder Materials
- Reduces Damaging Shock from Pumps to Critical Components
- Delivers an Even, Laminar Flow, and Continuous Chemical Dosage
- Pressure Rated at 150 PSI/10 Bar in All Sizes @ 70°F/23°C Non-Shock
- Made in USA

MATERIALS

- PVC Cell Class 12454 per ASTM D1784
- CPVC Cell Class 23447 per ASTM D1784
- Natural PVDF per ASTM D3222 Type 1
- Viton®, EPDM, Hypalon or PTFE Bladders


TECHNICAL INFORMATION
EXPLODED VIEW

SELECTION CHART

SIZE	CONNECTION SIZE	HOUSING MATERIAL	END CONNECTION	BLADDER / SEALS	PRESSURE RATING
006-6 in ³	1/2" (DN15)	PVC, CPVC or PVDF	NPT, BSPT, Flanged or True Union Socket	EPDM, Viton®, Hypalon or PTFE	150 PSI @ 70°F 10 Bar @ 21°C Non-Shock
010-10 in ³					
015-15 in ³					
029-29 in ³	3/4" (DN20)				
042-42 in ³					
036-36 in ³					
080-80 in ³					
125-125 in ³					

†PVC and CPVC housings have a non-wetted Noryl® top. PVDF housings have a non-wetted PVDF top.


HPD Series Pulsation Dampener

1/2" TO 1" PVC, CPVC OR PVDF

TECHNICAL INFORMATION, CONTINUED

PARTS LIST

1. Upper Housing, Noryl® or PVDF
2. Lower Housing, PVC, CPVC or PVDF
3. Bladder, EPDM, Viton®, Hypalon or PTFE
4. Charging Tee, Stainless steel
5. Air Valve Cap, Stainless steel
6. Pressure Gauge, Stainless steel



DIMENSIONS

SIZE	CONN. SIZE	A	B	C	D	E	F	G	H	J	K	L	M	N	WEIGHT
in ³	in	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm	in / mm	in	in / mm	in / mm	in / mm	in / mm	lbs / Kg
6	1/2	9.54 / 242	4.22 / 107	11.07 / 281	5.75 / 146	11.20 / 284	5.88 / 149	3.40 / 86	2.68 / 68	1/2	0.55 / 14	2.38 / 60	0.63 / 16	0.55 / 14	1.16 / 0.52
10	1/2	11.01 / 280	5.69 / 145	12.62 / 320	7.30 / 185	12.67 / 322	7.35 / 187	3.40 / 86	2.68 / 68	1/2	0.55 / 14	2.38 / 60	0.63 / 16	0.55 / 14	1.22 / 0.55
15	1/2	12.47 / 317	7.15 / 182	14.00 / 356	8.68 / 220	14.13 / 359	8.81 / 224	3.40 / 86	2.68 / 68	1/2	0.55 / 14	2.38 / 60	0.63 / 16	0.55 / 14	1.32 / 0.60
29	3/4	13.05 / 331	7.73 / 196	14.62 / 371	9.30 / 236	14.75 / 375	9.43 / 240	4.08 / 104	2.68 / 68	3/4	0.74 / 19	2.75 / 70	0.63 / 16	0.74 / 19	1.82 / 0.83
42	3/4	15.52 / 394	10.20 / 259	17.09 / 434	11.77 / 299	17.22 / 437	11.90 / 302	4.08 / 104	2.68 / 68	3/4	0.74 / 19	2.75 / 70	0.63 / 16	0.74 / 19	2.10 / 0.95
36	1	11.11 / 282	5.79 / 147	12.70 / 323	7.38 / 187	13.00 / 330	7.68 / 195	5.77 / 147	2.68 / 68	1	0.96 / 24	3.13 / 80	0.63 / 16	0.96 / 24	2.30 / 1.04
80	1	15.20 / 386	9.88 / 251	16.82 / 427	11.50 / 292	17.09 / 434	11.77 / 299	5.77 / 147	2.68 / 68	1	0.96 / 24	3.13 / 80	0.63 / 16	0.96 / 24	3.08 / 1.40
125	1	19.29 / 490	13.97 / 355	20.91 / 531	15.59 / 396	21.18 / 538	15.86 / 403	5.77 / 147	2.68 / 68	1	0.96 / 24	3.13 / 80	0.63 / 16	0.96 / 24	3.70 / 1.68

DAMPENER SIZING EQUATION

$$C(\text{in}^3) = \frac{(V) \times (K) \times (\text{SP}/\text{Pmin})^Y}{1 - (\text{SP}/\text{Pmax})^Y}$$

K = Type of Pump:
 Simplex: Single Acting = .60, Double Acting = .25
 Duplex: Single Acting = .25, Double Acting = .15
 Triplex: Single Acting = .15, Double Acting = .06


V = Volume/Stroke of Dosing Pump (in³)

SP = System Mean Operation Pressure

Pmin & Pmax = Min/Max Operating Pressure

Y = Compressed Charge in Dampener
 (Compressed Air / Nitrogen = 0.714)

OPERATING TEMPERATURE/PRESSURE



Hayward is a registered trademark of Hayward Industries, Inc.
 © 2022 Hayward Industries, Inc.

NPP1022

USA: 1.888.429.4635 • Fax: 1.888.778.8410 • One Hayward Industrial Drive • Clemmons, NC 27012 • Email: hfcsales@hayward.com
 Canada: 1.888.238.7665 • Fax: 1.905.829.3636 • 2880 Plymouth Drive • Oakville, ON L6H 5R4 • Email: hfcanada@hayward.com
 Visit us at: haywardflowcontrol.com

Authorised Distributor of Hayward Flow Control, a Division of Hayward Industries, Inc

Hayward Flow Control has been a leading manufacturer of industrial thermoplastic valves and process control products for more than 60 years. In fact, Hayward was one of the originators of the first thermoplastic ball valves. Since then, we have remained committed to producing the highest quality products while providing outstanding service.

Liquid Filters and Strainers



Bag Filter vessel

- GFPP
- PVC
- CPVC



Simplex Strainers

- PVC
- CPVC
- GFPP
- PVDF
- Eastar® (Clear)



Y Strainers

- PVC
- CPVC
- Clear PVC
- PVDF



Duplex Strainers

- PVC
- CPVC
- GFPP
- Eastar® (Clear)

Valves and Flow Control



Ball Valves

- PVC
- CPVC
- GFPP
- PVDF



Butterfly Valves

- PVC
- CPVC
- GFPP
- PP
- PVDF



Check Valves

- Ball Check Valves
- Y-Check Valves
- Wafer Check Valves
- Swing Check Valves



Actuation

- Electric
- Pneumatic



Pressure & Chemfeed

- Injection Quills
- Back Pressure
- Pressure Relief
- Diaphragm Valves
- Needle Valves
- Angle Globe Valves



Solenoid Valves

- PVC
- CPVC
- PVDF



Australia

Monarch Asia Pacific Pty Ltd
Unit 3
8 Bult Drive
Brendale, QLD 4500

Phone : +61 (0) 7 3889 9949

www.monarcindustrial.com.au



Thailand

PSF Equipment (Thailand) Co Ltd
11 Soi Suanphak 42
Suanphak Road, Chimphi
Talingchan, Bangkok 10170

Phone : +66 (0) 2 882 5512
Fax No: +66 (0) 2 424 3725

www.psfthailand.com